



PRODUCT No.: 1.410

VELO DE REFUERZO

POLYPROPYLENE VEIL FOR REINFORCEMENT

CHARACTERISTICS:

The **VELO DE REFUERZO** is a polypropylene fabric with excellent properties for reinforcing waterproofings where it's necessary to reinforce some areas or the whole surface. Its use allows improving impact resistance and improves the formation of bridges in cracks when waterproofing with elastic products to be applied in situ.

Weight	:	40 g/m ²
Thickness	:	0,43 mm
Elongation resistance		
Linear	:	> 55%
Horizontal	:	> 60 %
Fracture strength		
Linear	:	35 N/mm ²
Horizontal	:	35 N/mm ²

RANGE OF APPLICATION:

The **VELO DE REFUERZO** is applied when reinforcing acrylic and polyurethane waterproofings in order to reinforce terraces or façades, on areas such as cracks, extension joints, unions between floors and vertical walls or as a reinforcement for the whole waterproofing.

METHOD OF USE:

Apply the first coat of the liquid waterproofing agent and place the **VELO DE REFUERZO** on the applied coat. Press with the roller to soak it with the product. After the first coat is dry, apply the rest of the coats on the **VELO**.

PACKAGING:

The **VELO DE REFUERZO** is supplied in 1 m wide rolls.

ED.1999/1