



PRODUCT N°: 1.500

OLEOREPELENTE-BS

**ANTI-STAIN PROTECTION FOR TERRACOTTA, BAKED CLAY AND SURFACES
MADE OF POLISHED GRANITE AND MARBLE**

Characteristics:

OLEOREPELENTE-BS is a liquid product with a high vaporisation rate, which has been formulated based on polyfluorinated acrylic solvent-based copolymers. **Ready to use.** **OLEOREPELENTE-BS** is especially developed for **oil- and water-repellent** treatment on porous materials frequently used for paving, such as terracotta tiles and other types of paving manufactured with pressed and baked clay, which are usually found as paving in plenty of facilities.

Due to its special composition and its oil-repellent effect, it allows the treatment of kitchen surfaces made of polished granite and marble, providing them with a high anti-stain power, especially against stains due to oily products.

Applying **OLEOREPELENTE-BS** causes a repellent effect on the treated surfaces, thus producing a reduction in the absorption coefficients both for water and, especially, for oily materials, reducing their penetration in the substrate and the formation of persistent stains on those type of surfaces, mainly caused by spillage and splashing of oils and similar products.

Field of application:

OLEOREPELENTE-BS is especially recommended as treatment against formation of permanent stains on floors made of terracotta or other types of baked clay, which are presently very fashionable in plenty of facilities, restaurants, cafes, etc.

Treatment of polished granite and marble in order to provide them with protection against oily stains which are really frequent in kitchens due to spillage of oils and emulsions.

Method of use:

OLEOREPELENTE-BS should be always applied **pure**, as it's supplied. **Never dilute or mix** with any other product. The application of **OLEOREPELENTE-BS** can be made by roller, brush or spray; always on perfectly **clean and dry** surfaces.

In any of these methods of use, the whole of the surface should be treated and the support should be saturated with product. It's recommended to apply always **two coats** of product with the system **wet on wet** (leave about 10 – 15 minutes between both coats) in order to assure total saturation of the support.



When spraying (always with a low pressure) after the first spraying, let the chain go on for a few seconds, and then spray for the second time. This system is recommended when treating tiles in production lines.

The application of **OLEOREPELENTE-BS** forms no film coatings.

When applying on polished granite and marble surfaces, it's recommended to apply a small amount of product, directly or sprayed, on the surface to be treated which should be clean and dry, spreading it afterwards on the whole surface with a cloth soaked in **OLEOREPELENTE-BS**, thoroughly scrubbing in order to evenly spread the product. It's recommended to repeat the process when there were symptoms of oil permeability. Even when the application does not cause strong changes of colour in the materials to be treated, it is **necessary** to previously **test** before final application.

It's recommended not to use the treated floors until the product has totally polymerised, which takes place about 24 hours after application.

It's recommended to keep the containers tightly closed and in a cool and dry place, separated from every heat, fire or sparks source. Flammable product.

Packaging:

OLEOREPELENTE-BS is supplied in 10-25-50 and 200 liters metal containers.

Precautions:

* Easily flammable product. Irritates the eyes. Do not swallow. Keep away from the reach of children. Keep away from flames or sparks sources.

ADVANTAGES:

- **EASIER CLEANING.**
- **PREVENTS OILY PRODUCTS PENETRATION.**
- **KEEPS CLEANER FLOORS AND SURFACES.**
- **ALLOWS THE REMOVING OF SPILLAGES WITH NO STAIN FORMATION.**

ED.2001/1