

VIMELIN

Deshuttering coating for wooden and steel-faced formworks

Properties

VIMELIN is a deshuttering coating for wooden and steel-faced formworks based on petroleum.

VIMELIN acts both physically and chemically. It creates a thin film that cannot be removed by concrete and in addition, it reacts with the cement chemically, creating a thin separating crust. **VIMELIN**'s advantages are the following:

- > Particularly strong deshuttering action
- > Clean concrete surface, without any grease or oil residues
- > Perfect adhesion of the plaster and paint to the concrete surface
- > Avoidance of air bubbles in the surface of fair-faced concrete
- > Low cost due to extremely low consumption
- > Maintenance and protection of wooden and steel-faced formworks.

Applications

VIMELIN can be applied to all kind of form surfaces (wooden, steel-faced formworks). Apply it uniformly in the thinnest possible layer and on a clean form. Apply it using a brush or roll. For better results, spraying is recommended. **VIMELIN** is ready-mixed (not to be diluted) but must be shaken well before use.

Consumption

Depending on the type and absorption capacity of the coated surface, **50-100** g/m^2 are required.



Head: 1-3, Makedonias str, GR-546 41 Thessaloniki GREECE Tel: +30-2310 858561, +30-2310 843093 Fax: +30-2310843566 Branch: 8, Narkissou str, GR-136 72 Acharnes Attiki GREECE Tel: +30-210 2828435 Fax: +30-210 2829434 e-mail:info@vimatec.gr



Special Information

Storage: At least 12 months in sealed containers and in areas protected against frost. **Precautions-Hygiene Measures**: **VIMELIN** contains petroleum and thereby it is flammable and must be kept away from hearths of fire.



Head: 1-3, Makedonias str, GR-546 41 Thessaloniki GREECE Tel: +30-2310 858561, +30-2310 843093 Fax: +30-2310843566 Branch: 8, Narkissou str, GR-136 72 Acharnes Attiki GREECE Tel: +30-210 2828435 Fax: +30-210 2829434 e-mail:info@vimatec.gr

