

VIMEPOX SOLVENT

Special solvent for epoxy systems

Properties

VIMEPOX SOLVENT is a complex solvent (solvent mix) that is appropriate for epoxy systems.

Applications

VIMEPOX SOLVENT is convenient for dissolving or diluting epoxy materials. Specifically:

- Cleaning of surfaces and tools from VIMEPOX INJECT and MORTAR reparation materials, VIMEPOX F-COAT, SP-COAT, VIMEPOX FLOORING, VIMEPOX TOP-COAT coatings.
- Decreases the viscosity of VIMEPOX PRIMER-S, VIMEPOX F-COAT and VIMEPOX SP-COAT:

On surfaces with reduced absorbability and generally where a deeper penetration is needed, **VIMEPOX PRIMER-S** can be diluted up to 15% with **VIMEPOX SOLVENT**.

By dilution ratio of 10%, a primer may be produced to replace **VIMEPOX PRIMER-S** for **VIMEPOX F-COAT** and **SP-COAT** coatings.

How to use

VIMEPOX SOLVENT is used selfsame for the dilution of epoxy systems and the removal of resins.

However, dilution in water is recommended **only** for cleaning tools, e.g. removing epoxy colors.

1 part by volume **VIMEPOX SOLVENT**

1 part by volume water



VIMATEC - N. VIDALIS S.A. CONSTRUCTION CHEMICALS TECHNOLOGIES



Storing

The product can be stored in its sealed package for more that 12 months in places that are protected against high temperatures (<30° C).

Hygiene Measures-Precautions

- Always use protective goggles and gloves during the application of VIMEPOX SOLVENT.
- Always provide for proper ventilation during the application of this material indoors.
- > This material is flammable; its use near hearths of fire is not allowed

